

## Product Specification

# Single-Chamber Warming Cabinet

### Product Description

Belimed single-chamber warming cabinets are specifically designed for controlled temperature storage applications. The units, available in 7 sizes from tabletop to large stand-alone, consist of a directed airflow chamber with storage shelves, door, and a digital control and monitoring package.

### Application

For use in healthcare facilities to store blankets, IV infusion bags, or irrigation fluid at a controlled elevated temperature prior to use in a patient environment.

### Standard Features

#### Construction/Design

These cabinets employ solid stainless steel unit construction. They include 1-4 standard shelves (except SWC1518 & SWC1524), magnetic door closure gaskets, forced airflow, and levelling feet.

- Type 304 stainless steel cabinet
- Left and right stainless steel airflow plenums
- Fully insulated chamber to provide uniform heating
- Choice of solid stainless steel or transparent glass doors
- Available in stand-alone, recess, & pass-through configurations with adjustable feet
- Solid perforated stainless steel shelves
- Push button digital operation
- Digital control package, with large actual & setpoint LED displays, overtemperature audible/visual alarm, and keyed door/temperature lockout
- Powerful forced air heating elements. Independent digitally controlled heating chambers. Rapid warm time (2-6 hours depending on load)
- "Easy Log" integrated data logger with removable USB. Automatically records data every 30 minutes, Internal storage up to 2 years



### Benefits

#### Capacity to fit your needs

Since not all throughput requirements and available spaces are the same, Belimed offers a wide range of single-chamber sizes, ranging from compact tabletop to large freestanding units.

#### Durability

Beefy all-stainless construction guarantees long unit life, without corrosion or deformation. Easy to service slide-out electrical components make it easy to perform periodic system maintenance and upkeep.

#### Ease of use

Modern electronic controls make it easy to enter a temperature setpoint, but key lockout prevents unauthorized parameter alterations. Highly visible dual displays allow at-a-glance inspection of both actual and set temperatures. Audible/visual overtemperature alarm eliminates the possibility of overheated supplies being delivered to the surgical suite.

### Specifications

Model	Chamber Type	Storage Capacity (cu. ft.)	Exterior Dimensions, W x D x H (inches)	Shelves
SWC1518	Single	1.3	18.0 x 17.25 x 22.0	None std, 1 optional
SWC1824	Single	3.0	24.0 x 20.5 x 24.5	None std, 1 optional
SWC24	Single	5.27	30.0 x 26.5 x 24.5	1, adjustable
SWC36	Single	8.65	30.0 x 26.5 x 36.0	2, adjustable
SWC2460	Single	9.74	24.0 x 20.5 x 64.5	3, adjustable
SWC60	Single	13.05	30.0 x 20.5 x 64.5	3, adjustable
SWC72	Single	21.1	30.0 x 26.5 x 74.5	2, adjustable, 1, Fixed



For more information, visit [belimed.com](http://belimed.com)

# Single-Chamber Warming Cabinet

### Options/Accessories

#### Recess Mounting

- Side-panel delete
- 18" Depth
- Trim kit

#### Pass-through Mounting

- Pass-through chamber
- 18" Depth
- Trim kit

#### Door Configurations

- Factory installed left hinge with right swing
- Keyed door lock for intermediate & lower chamber units
- Solid-panel or full-view glass

#### Mobility

- Caster base
- Mobile base
- Mobile cabinet stands (tabletop models only)
- Mobile stands (tabletop models only)
- Roll-out baskets

#### Integrated Digital Temperature Recorder

- Integrated into unit controller
- Outputs data via standard USB receptacle
- Fully programmable for capture intervals and file size

#### Additional

- Electronic keypad lock
- Sloping top
- Seismic braces
- CuVerro® antimicrobial copper alloy handle

#### Premium Upgrade

- Ethernet/Wi-Fi capable TS-Series with intuitive touch screen and software



Mobile Stand



Cabinet Stand



Mobile Bases

---

Distributed by Belimed for Mac Medical

---

REV12.21.2020\_Q0

Engineers of Confidence.

**Belimed**  
Infection Control

Belimed, Inc.  
1.800.451.4118 | 1.843.216.7424  
[belimed.com](http://belimed.com)